



PRODUCT DATA: ELASTIC FIBER FILLER

DESCRIPTION:

Elastic putty composed of acrylic resins and glass fiber. Useful to fill and seal small cracks, cracks in ceilings and interior and exterior walls. Ideal to cover cracks and fissures with spatula or trowel on masonry surfaces, concrete, plaster, cement, etc ...

APPLICATION

Product suitable for interior and exterior use.

PROPERTIES AND CHARACTERISTICS

COLOUR: Natural white

DENSITY: 1.65 kg/l

VISCOSITY: 375 cps

FIBER CONTENT: 2%

DRYING TIME: Approx.3-4 hours each layer .

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product



PRODUCT DATA: ELASTIC FIBER FILLER

INSTRUCTIONS:

This product is sold ready to use and allows the sanding and painting. Regarding smoothing surfaces, it is advisable to always do it vertically from bottom to top. Always place excess material and then remove the excess. When the material dries, sand and then apply another layer of plaster horizontally from right to left. For a flawless finish, the surface should be sanded after the second layer and painted with PRODEPA paint.

PACKAGING:

Packet: 1 Kg or 5 Kg

CAUTIONS:

Do not apply under 5°C or over 50°C in the sun. Keep containers out of direct radiation. Keep out of reach of children.

